


ROBESLEE**CONCRETE**

COMPOSITE LINTELS (TYPE B)



Declaration of Performance No. B/01

Unique identification code of the product-type:
Type A Prestressed Lintel (145x70)

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
Prestressed Lintel to be used as a composite lintel in walls and partitions

Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):
Robeslee Concrete, Southbank Rd, Kirkintilloch, Glasgow, G66 1UB

System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:
System 3

Declaration of performance concerning covered by a harmonised standard:

BS EN 845-2:2003

CERAM, Queens Rd, Penkhull, Stoke-on-Trent, ST4 7LQ (Notified Body No : 1289) - 8.2 Initial Type Testing

Essential characteristics	Performance		Harmonised technical specification
Load Bearing Capacity	Lintel Length (mm)	Load at Deflection Effective Span/325 (kN)	EN 845-2:2003
	900	16.1	
	1800	6.97	
	2700	3.67	
Water Absorption	NPD		
Water Vapour Permeability	NPD		
Direct Airborne Sound Insulation	28 kg/m ²		
Thermal Resistance	1.72 W/(m·K)		
Water absorption	NPD		
Resistance to Fire	R 30		
Durability of performance (against corrosion)	Material/Coating Reference C Number 2		
Dangerous Substance	NPD		

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Issued By: Steven Black (Operations Manager)

Date: 14/10/2016

Steven Black

P:0141 775 2677

E: info@robesslee.co.uk