



COMPOSITE LINTELS (TYPE A)



Declaration of Performance No. A/01

Unique identification code of the product-type:
Type A Prestressed Lintel (100x65)

Intended use or uses of the construction product, in accordance with the applicable Designated technical specification, as foreseen by the manufacturer:
Prestressed Lintel to be used as a composite lintel in walls and partitions

Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):
Robeslee Concrete, Southbank Rd, Kirkintilloch, Glasgow, G66 1UB

System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:
System 3

Declaration of performance concerning covered by a Designated standard:
**BS EN 845-2:2003+A1:2016
CERAM, Queens Rd, Penkhull, Stoke-on-Trent, ST4 7LQ (Notified Body No : 1289) - 8.2 Initial Type Testing**

Essential characteristics	Performance		Designated technical specification
Load Bearing Capacity	Lintel Length (mm) no brickwork	Load at Deflection Effective Span/325 (kN)	EN 845-2:2003+A1:2016
	900	7.90	
	1050		
	1200		
	1500		
	1800	3.93	
	2100		
	2400		
	2700	2.00	
3600			
Water Absorption	NPD		
Water Vapour Permeability	NPD		
Direct Airborne Sound Insulation	20 kg/m ²		
Thermal Resistance	1.72 W/(m·K)		
Water absorption	NPD		
Resistance to Fire	R 30		
Durability of performance (against corrosion)	Material/Coating Reference C Number 2		
Dangerous Substance	NPD		

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

This declaration of conformance is issued, in accordance with Regulation (EU) No 305/2011, as it has effect in the United Kingdom under the sole responsibility of the manufacturer identified above.

Issued By: Steven Black (Operations Manager) **Date:** 06/04/2021 **Place:** Southbank Rd, Glasgow, G66 1UB

Steven Black